





### SAVE MONEY!

Buy Direct From the Manufacturer No Middle Man~







\* EASY TO USE

Pro-Seal 6006 is self leveling and can be poured into the loop slot. No expensive pump systems or special caulking guns are required. Eliminate equipment and equipment maintenance!

\* FAST

A typical 6' x 60' quadrapole loop can be sealed in a matter of minutes! No pump system to clean or repair at the end of the day. Save both time and money with Pro-Seal 6006.

RAPID CURE

Cures in only 10-15 minutes! Open up the lane to traffic and move on to the next loop without pick-up or tracking.

\* OUTSTANDING PROTECTION

Pro-Seal 6006 encapsulates, insulates and protects. Loop wires are held in position and completely protected from movement, road debris and moisture. Pro-Seal 6006 does not shrink, which eliminates refilling call-backs.

"PROPERLY INSTALLED LOOPS ARE THE MOST RELIABLE MEANS OF VEHICLE DETECTION."

Manufactured in the USA by RAI Products.

# EASY





## MANUFACTURED RAI Products BY RAI PRODUCTS

## WE HAVE FILE GURE

PRO-SEAL 6006 is an easy to use polyester sealant, available in convenient one gallon cans. PRO-SEAL 6006 eliminates the need for costly pump systems and slow pneumatic caulking guns, which can cause maintenance headaches.

### ADDING CATALYST

For one gallon, just add two 1oz. tubes of catalyst. (Included)



### MIXING SEALANT

Completely mix contents of can from bottom up. For best results, use a powered mixer. Mix until a uniform color is achieved and there are no visible streaks of red catalyst. (Normal mix time is 1-3 minutes.)



## **APPLYING SEALANT**

Pour pre-mixed PRO-SEAL 6006 into loop slot, encapsulating the loop wires. Smooth sealant into the saw slot with a squeegee.







Manufactured in the USA by RAI Products.

## PHYSICAL PROPERTIES

**SEALANT TYPE:** 

COLOR:

TACK FREE TIME:

COMPLETE CURE:

TENSILE STRENGTH:

TENSILE ELONGATION:

PACKAGING:

Polyester

**Dark Brown** 

10-15 Minutes (@77°F)

1 hour

1,130 PSI

15% Minimum

4 Gals./Case ~ with Catalyst

PRO	DEPTH	WIDTH		
FRU		1/8"	1/4"	3/8"
CEAL	1"	160'	80'	53'
SEAL	1 1/2"	120'	60'	39'
1 GALLON COVERAGE	2"	80'	40'	26'



TESTIMONY - "...Out of all the sealants I've used in the past, PRO-SEAL 6006 is by far the best, and believe me I have used them all. PRO-SEAL can be applied very quickly and cures in just a few minutes, allowing my crew to open the lane up and move on to the next loop. We can seal a typical 6' x 60' quadrapole loop in about 5 minutes using PRO-SEAL 6006." Terry Spell, President, Terry Spell Mechanical Services



SAME DAY SHIPPING



RAI

RAI Products

Since 1954

Website - www.raiproducts.com E-mail - info@raiproducts.com PO Box 240772 - Charlotte, NC 28224 (704) 525-1852 - Fax (704) 525-1859